



1 844 842 5141

info@bigfootcrane.com

www.bigfootcrane.com

Bigfoot Crane Company has taken innovation to new heights by collaborating with Boscaro to design modular lifting frames, adapting the original EZBar spreader bar design and enhancing the functionality of their proprietary modular spreader bars. This new product aims to address the unique challenges posed by lifting and hoisting operations in various industries.

The new lifting frame, achieved by linking the spreader bars sections to corner frames, seamlessly integrate with EZBar Spreader Bars, creating a robust lifting frame that ensures optimal load distribution and stability. This innovative design not only enhances the overall performance of the lifting equipment but also demonstrates the commitment of both companies to providing cutting-edge solutions for the evolving needs of the lifting and construction industry.

With the introduction of these modular lifting frames, Bigfoot Crane Company continues to redefine standards in crane technology and contribute to safer and more efficient lifting operations.

Features

- ⊗ Range from 1.31M/4′ to 10.36M/34′
- Lifting Capacities up to 110 Tonnes/242,506lbs
- Reduces the need for multiple spreader bars and decrease head room needed from crane hook to the top of the load
- Increased stability during lifting operations
- Evenly distributes the load across multiple lifting points.
- Adaptable for various lifting applications
- Reduces the likelihood of load tilting or misalignment.







1 844 842 5141

info@bigfootcrane.com

www.bigfootcrane.com

Model		15T Frame 1×1	15T Frame 1×3/2×2	15T Frame 1×5/2×4/3×3	15T Frame 3×5/4×4	15T Frame 5×5
Capacity	Min. Capacity	33,070 lbs	17,637 lbs	6,614 lbs	6,614 lbs	6,614 lbs
	Max. Capacity	33,070 lbs	26,455 lbs	17,637 lbs	16,535 lbs	13,228 lbs
Dimentions	Min. Length	5'10"	6'7"	10'4"	10'11"	14'7"
	Min. Width	5'11"	5'11"	5'11"	10'1"	14'4"
	Max. Length	5'10"	13'1"	20'4"	20'4"	20'4″
	Max. Width	5'11"	9'6"	13'1"	16'8″	20'4"
Male X1	EZBar-12T	2	4	6	8	10
Female X1	EZBar 15T	2	4	6	8	10
Assembly Pin	15T-Pin	12	20	28	36	44
Spreader Bar Frame Corners	EZBar 15T- Corner	4	4	4	4	4







1 844 842 5141

🔀 info@bigfootcrane.com

www.bigfootcrane.com

Model		35T Frame 1×1	35T Frame 1×3/2×2	35T Frame 1×5/2×4/3×3	35T Frame 3×5/4×4	35T Frame 5×5
Capacity	Min. Capacity	77,162 lbs	50,706 lbs	15,432 lbs	15,432 lbs	15,432 lbs
	Max. Capacity	77,162 lbs	74,957 lbs	66,139 lbs	44,092 lbs	39,683 lbs
Dimentions	Min. Length	8'6″	11'6″	17'9″	20'7"	24'9″
	Min. Width	9'9"	9'9"	9'9″	18'9″	27'10"
	Max. Length	8'6″	21'9″	35'0"	35'0"	35'0″
	Max. Width	9'9"	15'9″	23'0″	29'0″	46'4″
Male X1	EZBar-12T	2	4	6	8	10
Female X1	EZBar 15T	2	4	6	8	10
Assembly Pin	15T-Pin	16	24	32	40	48
Spreader Bar Frame Corners	EZBar 15T- Corner	4	4	4	4	4







1 844 842 5141

info@bigfootcrane.com

www.bigfootcrane.com

Model		110T Frame 1×1	110T Frame 1×3/2×2	110T Frame 1×5/2×4/3×3	110T Frame 3×5/4×4	110T Frame 5×5
Capacity	Min. Capacity	242,508 lbs	171,961 lbs	59,525 lbs	59,525 lbs	59,525 lbs
	Max. Capacity	242,508 lbs	238,099 lbs	198,416 lbs	110,231 lbs	97,003 lbs
Dimentions	Min. Length	10'6"	12'2"	16'11"	21'3″	25'5″
	Min. Width	9'2"	10'3"	10'3"	19'6"	28'6″
	Max. Length	10'6"	22'3″	35'8″	35'8″	35'8″
	Max. Width	9'2"	16'5″	22'5″	29'0"	37'0″
Male X1	EZBar-12T	2	4	6	8	10
Female X1	EZBar 15T	2	4	6	8	10
Assembly Pin	15T-Pin	16	24	32	40	48
Spreader Bar Frame Corners	EZBar 15T- Corner	4	4	4	4	4

