

SAFE EFFICIENT STRONG



Boscaro's EZ™ Spreader Bar systems have been fully tested for compliance with ASME, eliminating the need for an assortment of bars while allowing you to adapt to the changing demands of your job site. With male and female interlocking components, the unique design provides multiple configurations. Utilize each section as an individual bar or combine components to form an adjustable spreader bar with 1' increments.

The lightweight build and the option to disassemble the components not only increases your capacity but also makes transportation, assembly, and storage of the system simple and time efficient. Components are galvanized which increases durability and prevents paint chips due to repetitive movement. With Boscaros' EZ Spreader Bars you will be improving efficiency on site as well as managing down costs.



☎ 1 844 842 5141

✉ info@bigfootcrane.com

🌐 www.bigfootcrane.com

Special Update:

Due to highly fluctuating steel prices, Bigfoot Crane Company reserves the right to change its pricing to reflect these changes at any time, and on any open quote issued. We understand this may result in unexpected cost fluctuation, and we are doing everything possible to reduce impact on our customers.

If you have questions, concerns or to get a quote please call 1-855-598-3915.

**Thank you for your
understanding in this
matter.**



SAFE EFFICIENT STRONG



📞 1 844 842 5141

✉ info@bigfootcrane.com

🌐 www.bigfootcrane.com

Features

- ✓ Modular Spreader Bar System
- ✓ Range from 1.31M/4' to 10.36M/34'
- ✓ Lifting Capacities up to 110 Tonnes/242,506lbs
- ✓ Galvanized for Durability
- ✓ Easily Transported & Stored

Specifications			
Model	15T EZ Bar System	35T EZ Bar System	110T EZ Bar System
Min Length	4'	8'	8'
Max Capacity	33,070 lbs	77,161 lbs	242,506 lbs
Ext. Length	16.5'	34'	34'
Ext. Capacity	6613 lbs	15,432 lbs	59,424 lbs

*Capacity is based off a 60 degree sling angle

