SAFE EFFICIENT STRONG



Engineered for job sites that demand quick adjustments, high performance, and unmatched safety, the Boscaro ESB Telescopic Spreader Bars deliver a fixed lifting capacity across all configurations, making them ideal for lifting long, awkward, or heavy loads with confidence and precision.

The ESB-15 and ESB-30 offer a telescoping feature that eliminates the need for additional components or reconfiguration on site. Adjust your spreader bar length without tools, saving valuable time on every lift. This plug-and-play modularity makes it ideal for construction, shipping yards, heavy equipment handling, and general industrial use.



1844 842 5141

≥ info@bigfootcrane.com

www.bigfootcrane.com

Special Update:

Due to highly fluctuating steel prices, Bigfoot Crane Company reserves the right to change its pricing to reflect these changes at any time, and on any open quote issued. We understand this may result in unexpected cost fluctuation, and we are doing everything possible to reduce impact on our customers.

If you have questions, concerns or to get a quote please call 1-855-598-3915.

Thank you for your understanding in this matter.





SAFE EFFICIENT STRONG





1844 842 5141

info@bigfootcrane.com

www.bigfootcrane.com

Features

- ⊗ Range from 2.7M/8.86′ to 6M/19.68′
- ⊗ Lifting Capacities up to 30 Tonnes/66,138 lbs

- ⊗ Hot-Dip Galvanized Finish

Specifications		
Model	ESB-15	ESB-30
Min Length	8.85'	11.97′
Max Capacity	33,070 lb	66,138 lb
Ext. Length	14.1′	19.68′
Ext. Capacity	33,070 lb	66,138 lb

^{*}Capacity is based off a 60 degree sling angle